



Dimension (mm)

Coating Color - Black



Type	Dimensions (mm)				
	L. (Max)	H. (Max)	Pitch.	d	h
HV1W2P8J	23.5	6.5	20.3 ± 0.5	0.5±0.1	3.5+0.1-0.3
HV122P7J	21.0		17.8 ± 0.5	0.5±0.1	3.5+0.1-0.3
HV122P6J	18.0	5.08	15.2 ± 0.2	0.5±0.1	3.5+0.1-0.3
HV122P5J	15.3		12.7 ± 0.2	0.5±0.1	3.5+0.1-0.3
HV122P4J	12.7		10.2 ± 0.2	0.5±0.1	3.5+0.1-0.3

How To Order

HV	1W	2P	8	J
High Voltage	Watt	Number of Pin	Pitch (inches)	Tolerance

Specifications given herein may be changed at time without prior notice, Please confirm technical specifications before your order / or use.

Rating

Type	Power Rating	Max Working Voltage	T.C.R.	Resistance Range(Ω)	Resistance Tolerance	Rated Ambient Temp.	Operating Temp. Range		
HV1W2P8J	1W	10KV	±300ppm (°C)	10M ~ 100M	J:±5%, K:±10%	±70℃	-25℃ to 125℃		
HV122P7J	0.5W			20M ~ 200M					
HV122P6J				1M ~ 20M	G:±2%				
HV122P5J				2M ~ 200M				J:±5%, K:±10%	
HV122P4J	1KV			2M ~ 10M	F:±1%, G:±2%				

The Max. Working voltage requested to applied as rature when a calculated rated voltage exceeds it.
Consult with us about the availability of resistors with resistance values and tolerances which are outside the ranges given above and of a special shape.


☆高壓厚膜電阻器 THICK FILM RESISTORS FOR HIGH VOLTAGE ☆



Glass Coating Tyle



Dimensions (mm)



TYPE	DIMENSION (mm)		
	L MAX.	H MAX.	P
HV2W2P8X	20.32	9.0	20.3±0.5
HV2W2P8X	20.32	9.0	20.3±0.5
HV2W2P8X	20.32	9.0	20.3±0.5

■ RATING

TYPE	POWER RATING	MAX. WORKING VOLTAGE	T.C.R	RESISTANCE RANGE (Ω)	RESISTANCE TOLERANCE	RATED AMBIENT TEMP.	OPERATING TEMP. RANGE
HV2W2P8X	2W	13KV	(±300ppm/C)	500M	K(±10%)	(+70C)	(-25C to +125C)
HV2W2P8X	2W	15KV	(±300ppm/C)	100M	K(±10%)	(+70C)	(-25C to +125C)
HV2W2P8X	2W	22KV	(±300ppm/C)	2000M	K(±15%)	(+70C)	(-25C to +125C)

★ CONSULT WITH US ABOUT THE AVAILABILITY OF RESISTORS WITH RESISTANCE VALUES AND TOLERANCES WHICH ARE OUTSIDE THE RANGES GIVEN ABOVE AND OF A SPECIAL SHAPE.

■ HOW TO ORDER

HV	18	2P	8	K
SERIES	WATTES	NUMBER OF PINS	Pitches (mm)	TOLERANCE

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before your order/or use.